SUSPENSION AND COMPONENTS › SUSPENSION TUBES AND COMPONENTS › SUSPENSION TUBES

# SUSPENSION TUBE

Scalloped · 9 in Long · 3/8-24 in Female Thread · Aluminum · Black Anodized / Natural

PART NUMBER
**QRP38-090**



## OVERVIEW

QuickCar Scalloped Suspension Tubes provide a lightweight, rigid connection for adjustable suspension and chassis systems where strength, accuracy, and easy setup changes are essential. Manufactured from 6061 aluminum with a distinctive scalloped design, these tubes deliver increased strength compared with traditional hex or round suspension tubes while keeping unnecessary weight out of the chassis. Precision-machined ends provide accurate fitment with compatible rod ends and suspension hardware, helping maintain consistent geometry and dependable adjustment.

The scalloped profile provides convenient gripping surfaces for making suspension changes by hand or with a wrench, while clearly identified left-hand threads make adjustments faster and less confusing in the shop or at the track. Finished for corrosion resistance and built for demanding racing environments, QuickCar Scalloped Suspension Tubes give racers a strong, lightweight, and easily adjustable foundation for fine-tuning suspension and chassis setup.

## SPECIFICATIONS

| | |
|---|---|
| Style | **Scalloped** |
| Material | **Aluminum** |
| Finish | **Black Anodized** |
| Tube Length | **9 Inch** |
| Sold As | **Each** |

## SHIPPING & PACKAGING

| | |
|---|---|
| Package | **9.95 × 1.05 × 0.65 in** |
| Ship Weight | **0.17 lb** |
| Country of Origin | **USA** |
| Vehicle Type | **Car** |

## ALSO AVAILABLE IN THIS FAMILY (33 PART NUMBERS)

| PART # | TUBE LENGTH | WT. |
|---|---|---|
| QRP38-080 | 8 in | 0.15 lb |
| QRP38-085 | 8.5 in | 0.17 lb |
| ▶ QRP38-090 | 9 in | 0.17 lb |
| QRP38-095 | 9.5 in | 0.18 lb |
| QRP38-100 | 10 in | 0.2 lb |
| QRP38-105 | 10.5 in | 0.21 lb |
| QRP38-110 | 11 in | 0.2 lb |
| QRP38-115 | 11.5 in | 0.23 lb |
| QRP38-120 | 12 in | 0.23 lb |
| QRP38-125 | 12.5 in | 0.25 lb |
| QRP38-130 | 13 in | 0.26 lb |
| QRP38-135 | 13.5 in | 0.27 lb |
| QRP38-140 | 14 in | 0.28 lb |
| QRP38-145 | 14.5 in | 0.29 lb |
| QRP38-150 | 15 in | 0.29 lb |
| QRP38-155 | 15.5 in | 0.3 lb |
| QRP38-160 | 16 in | 0.32 lb |
| QRP38-165 | 16.5 in | 0.33 lb |
| QRP38-170 | 17 in | 0.34 lb |
| QRP38-175 | 17.5 in | 0.35 lb |
| QRP38-180 | 18 in | 0.37 lb |
| QRP38-185 | 18.5 in | 0.42 lb |
| QRP38-190 | 19 in | 0.39 lb |
| QRP38-195 | 19.5 in | 0.4 lb |
| QRP38-200 | 20 in | 0.41 lb |
| QRP38-210 | 21 in | 0.43 lb |
| QRP38-220 | 22 in | 0.45 lb |
| QRP38-230 | 23 in | 0.48 lb |
| QRP38-240 | 24 in | 0.49 lb |
| QRP38-250 | 25 in | 0.55 lb |
| QRP38-260 | 26 in | 0.54 lb |
| QRP38-270 | 27 in | 0.57 lb |
| QRP38-280 | 28 in | 0.58 lb |

▶ Highlighted row is the part on this sheet.



▲ WARNING: Cancer and Reproductive Harm — www.P65Warnings.ca.gov