

SUSPENSION AND COMPONENTS > SUSPENSION TUBES AND COMPONENTS > SUSPENSION TUBES

SUSPENSION TUBE

Scalloped · 18.5 in Long · 5/8-18 in Female Thread · Aluminum · Black Anodized / Natural

PART NUMBER
QRP62-185



OVERVIEW

QuickCar Scalloped Suspension Tubes provide a lightweight, rigid connection for adjustable suspension and chassis systems where strength, accuracy, and easy setup changes are essential. Manufactured from 6061 aluminum with a distinctive scalloped design, these tubes deliver increased strength compared with traditional hex or round suspension tubes while keeping unnecessary weight out of the chassis. Precision-machined ends provide accurate fitment with compatible rod ends and suspension hardware, helping maintain consistent geometry and dependable adjustment.

The scalloped profile provides convenient gripping surfaces for making suspension changes by hand or with a wrench, while clearly identified left-hand threads make adjustments faster and less confusing in the shop or at the track. Finished for corrosion resistance and built for demanding racing environments, QuickCar Scalloped Suspension Tubes give racers a strong, lightweight, and easily adjustable foundation for fine-tuning suspension and chassis setup.

SPECIFICATIONS

Thread Size	5/8 Inch-18	Package	20.3 × 1.65 × 1.25 in
Style	Scalloped	Ship Weight	1.01 lb
Material	Aluminum	Country of Origin	USA
Finish	Black Anodized	Vehicle Type	Car
Tube Length	18.5 Inch		
Sold As	Set of 10		

SHIPPING & PACKAGING

ALSO AVAILABLE IN THIS FAMILY (45 PART NUMBERS)

PART #	TUBE LENGTH	WT.	PART #	TUBE LENGTH	WT.	PART #	TUBE LENGTH	WT.
QRP62-070	7 in	0.34 lb	QRP62-145	14.5 in	0.75 lb	QRP62-220	22 in	1.14 lb
QRP62-075	7.5 in	0.37 lb	QRP62-150	15 in	0.77 lb	QRP62-225	22.5 in	1.17 lb
QRP62-080	8 in	0.4 lb	QRP62-155	15.5 in	0.79 lb	QRP62-230	23 in	1.2 lb
QRP62-085	8.5 in	0.41 lb	QRP62-160	16 in	0.83 lb	QRP62-235	23.5 in	1.15 lb
QRP62-090	9 in	0.45 lb	QRP62-165	16.5 in	0.85 lb	QRP62-240	24 in	1.25 lb
QRP62-095	9.5 in	0.48 lb	QRP62-170	17 in	0.88 lb	QRP62-280	28 in	1.51 lb
QRP62-100	10 in	0.5 lb	QRP62-175	17.5 in	0.9 lb	QRP62-310	31 in	1.75 lb
QRP62-105	10.5 in	0.53 lb	QRP62-180	18 in	0.93 lb	QRP62-457	45.75 in	2.4 lb
QRP62-110	11 in	0.56 lb	► QRP62-185	18.5 in	1.01 lb	QRP62-465	46.5 in	2.4 lb
QRP62-115	11.5 in	0.59 lb	QRP62-190	19 in	0.98 lb	QRP62-477	47.75 in	2.5 lb
QRP62-120	12 in	0.61 lb	QRP62-195	19.5 in	0.99 lb	QRP62-480	48 in	2.6 lb
QRP62-125	12.5 in	0.63 lb	QRP62-200	20 in	1.03 lb	QRP62-487	48.75 in	2.55 lb
QRP62-130	13 in	0.67 lb	QRP62-205	20.5 in	1.02 lb	QRP62-490	49 in	2.6 lb
QRP62-135	13.5 in	0.7 lb	QRP62-210	21 in	1.1 lb	QRP62-500	50 in	2.7 lb
QRP62-140	14 in	0.72 lb	QRP62-215	21.5 in	1.12 lb	QRP62-510	51 in	2.7 lb

► Highlighted row is the part on this sheet.