SUSPENSION AND COMPONENTS › SUSPENSION TUBES AND COMPONENTS › SUSPENSION TUBES

SUSPENSION TUBE

Scalloped · 39 in Long · 3/4-16 in Female Thread · Aluminum · Black Anodized / Natural

PART NUMBER
QRP75-390



OVERVIEW

QuickCar Scalloped Suspension Tubes provide a lightweight, rigid connection for adjustable suspension and chassis systems where strength, accuracy, and easy setup changes are essential. Manufactured from 6061 aluminum with a distinctive scalloped design, these tubes deliver increased strength compared with traditional hex or round suspension tubes while keeping unnecessary weight out of the chassis. Precision-machined ends provide accurate fitment with compatible rod ends and suspension hardware, helping maintain consistent geometry and dependable adjustment.

The scalloped profile provides convenient gripping surfaces for making suspension changes by hand or with a wrench, while clearly identified left-hand threads make adjustments faster and less confusing in the shop or at the track. Finished for corrosion resistance and built for demanding racing environments, QuickCar Scalloped Suspension Tubes give racers a strong, lightweight, and easily adjustable foundation for fine-tuning suspension and chassis setup.

SPECIFICATIONS

Style	**Scalloped**
Material	**Aluminum**
Finish	**Black Anodized**
Tube Length	**39 Inch**
Sold As	**Each**

SHIPPING & PACKAGING

Package	**39 × 1.25 × 1.25 in**
Ship Weight	**2.45 lb**
Country of Origin	**USA**
Vehicle Type	**Car**

ALSO AVAILABLE IN THIS FAMILY (56 PART NUMBERS)

PART #	TUBE LENGTH	WT.
QRP75-070	7 in	0.41 lb
QRP75-075	7.5 in	0.44 lb
QRP75-080	8 in	0.47 lb
QRP75-085	8.5 in	0.5 lb
QRP75-090	9 in	0.55 lb
QRP75-095	9.5 in	0.56 lb
QRP75-100	10 in	0.6 lb
QRP75-105	10.5 in	0.64 lb
QRP75-110	11 in	0.66 lb
QRP75-115	11.5 in	0.7 lb
QRP75-120	12 in	0.74 lb
QRP75-125	12.5 in	0.76 lb
QRP75-130	13 in	0.8 lb
QRP75-135	13.5 in	0.82 lb
QRP75-140	14 in	0.92 lb
QRP75-145	14.5 in	0.89 lb
QRP75-150	15 in	0.92 lb
QRP75-155	15.5 in	1.01 lb
QRP75-160	16 in	0.98 lb
QRP75-165	16.5 in	1.01 lb
QRP75-170	17 in	1.06 lb
QRP75-175	17.5 in	1.06 lb
QRP75-180	18 in	1.17 lb
QRP75-185	18.5 in	1.14 lb
QRP75-190	19 in	1.19 lb
QRP75-195	19.5 in	1.22 lb
QRP75-200	20 in	1.25 lb
QRP75-205	20.5 in	1.27 lb
QRP75-210	21 in	1.32 lb
QRP75-215	21.5 in	1.34 lb
QRP75-220	22 in	1.39 lb
QRP75-225	22.5 in	1.42 lb
QRP75-230	23 in	1.44 lb
QRP75-235	23.5 in	1.55 lb
QRP75-240	24 in	1.55 lb
QRP75-250	25 in	1.65 lb
QRP75-260	26 in	1.75 lb
QRP75-270	27 in	1.75 lb
QRP75-280	28 in	1.8 lb
QRP75-290	29 in	1.9 lb
QRP75-300	30 in	1.9 lb
QRP75-310	31 in	1.97 lb
QRP75-320	32 in	1.95 lb
QRP75-330	33 in	2.1 lb
QRP75-340	34 in	2.2 lb
QRP75-350	35 in	2.2 lb
QRP75-360	36 in	2.3 lb
QRP75-370	37 in	2.35 lb
QRP75-380	38 in	2.35 lb
▶ QRP75-390	**39 in**	**2.45 lb**
QRP75-400	40 in	2.6 lb
QRP75-410	41 in	2.6 lb
QRP75-420	42 in	2.65 lb
QRP75-430	43 in	2.7 lb
QRP75-440	44 in	2.8 lb
QRP75-600	72 in	4.7 lb

▶ Highlighted row is the part on this sheet.

▲ WARNING: Cancer and Reproductive Harm — www.P65Warnings.ca.gov